

# Product datasheet

Specifications



## Easy UPS 3M Advanced 100kW scalable to 150kW 400V for external batteries, Start-up 5x8

E3MUPS100K150HINS

### Overview

**Lead time** Usually Ships within 2 Weeks

### Main

**Main Input Voltage** 400 V AC 3 phases  
415 V AC 3 phases

**Input voltage** 400 V

**Output voltage** 400 V AC 3 phases

**Rated power in W** 100 kW

**rated power in VA** 100 kVA

### Complementary

**Battery type** Lead-acid external  
Li-Ion (Lithium-Ion) external

**Colour** White

**Height** 197 cm

**Width** 60.8 cm

**Depth** 100.8 cm

**Product weight** 306 kg

**USB compatible** Yes

**Redundant** Yes

**Range of product** Easy UPS 3M

**Product or component type** Uninterruptible power supply (UPS)

### Batteries & Runtime

**Battery type** VRLA  
Li-Ion (Lithium-Ion)

### Packing Units

**Unit Type of Package 1** PCE

**Number of Units in Package 1** 1

**Package 1 Height** 213 cm

**Package 1 Width** 75 cm

**Package 1 Length** 119 cm

**Package 1 Weight** 354 kg

# Contractual warranty

---

Warranty (in months)

12



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

SCIP Number

65871482-995d-4fb8-960b-f71cf07ec0ba

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

Take-back

Nej

Image of product / Alternate images

Alternative

---





