

# Product datasheet

Specifications



## Easy UPS 3M Advanced 100kW scalable to 250kW 400V for external batteries, Start-up 5x8

E3MUPS100K250HINS

### Overview

Lead time Usually Ships within 2 Weeks

### Main

Main Input Voltage 400 V AC 3 phases  
415 V AC 3 phases

Input voltage 400 V

Output voltage 400 V AC 3 phases

### Complementary

Battery type Lead-acid external

Colour White

Redundant Yes

Range of product Easy UPS 3M

Product or component type Uninterruptible power supply (UPS)

### Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 213 cm

Package 1 Width 75 cm

Package 1 Length 119 cm

Package 1 Weight 360 kg

### Contractual warranty

Warranty (in months) 12

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

SCIP Number

65871482-995d-4fb8-960b-f71cf07ec0ba

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

Take-back

No

Image of product / Alternate images

Alternative

---





